

# OIL SUCTION & DISCHARGE HOSE 150PSI



<b>Applications</b>	For suction and discharge of petroleum products, of up to 50% aromatic contents, in refineries, factories and vessels.
<b>Tube</b>	Oil resistant synthetic rubber
<b>Reinforcement</b>	High tensile synthetic fabric with steel helical embedded wire
<b>Cover</b>	Weather, ozone and oil resistant synthetic rubber
<b>Marking</b>	<b>JNTER OSD150 OIL SUCTION &amp; DISCHARGE HOSE - BP 450PSI - WP 150PSI</b>



Smooth



Nominal ID		ID	OD	WP		BP		Product code	
Inch	mm	mm	mm	bar	PSI	bar	PSI	40M	60M
1	25	25.4	36.4	10	150	30	450	BI-51101	BI-61101
1.1/4	32	32.0	43.0	10	150	30	450	BI-51102	BI-61102
1.1/2	38	38.0	50.0	10	150	30	450	BI-51103	BI-61103
2	51	50.8	62.8	10	150	30	450	BI-51104	BI-61104
2.1/2	63	63.5	78.3	10	150	30	450	BI-51105	BI-61105
3	76	76.2	91.0	10	150	30	450	BI-51106	BI-61106
3.1/2	90	88.9	103.7	10	150	30	450	BI-51107	BI-61107
4	102	101.6	117.6	10	150	30	450	BI-51108	BI-61108
5	127	127.0	147.8	10	150	30	450	BI-51109	BI-61109
6	152	152.4	175.2	10	150	30	450	BI-51110	BI-61110

\*For sizes other than listed above, please contact us\*

Flat-Corrugated



Nominal ID		ID	OD	WP		BP		Product code	
Inch	mm	mm	mm	bar	PSI	bar	PSI	40M	60M
1.1/4	32	32.0	42.8	10	150	30	450	BI-21002	BI-61102C
1.1/2	38	38.0	51.0	10	150	30	450	BI-21003	BI-61103C
2	51	50.8	62.6	10	150	30	450	BI-21004	BI-61104C
2.1/2	63	63.5	77.9	10	150	30	450	BI-21005	BI-61105C
3	76	76.2	90.6	10	150	30	450	BI-21006	BI-61106C
3.1/2	90	88.9	104.0	10	150	30	450	BI-21007	BI-61107C
4	102	101.6	120.0	10	150	30	450	BI-21008	BI-61108C
5	127	127.0	148.0	10	150	30	450	BI-21009	BI-61109C
6	152	152.4	175.2	10	150	30	450	BI-21010	BI-61110C

\*For sizes other than listed above, please contact us\*