

Hinet Hose


Features

- Excellent transparency making it possible to confirm the contents.
- No elongation observed under pressure due to warp reinforcement.
- Excels in cold resistance, heat resistance, and chemical resistance.
- Complies with Standard of Apparatus, Containers and Packaging based on Japanese Ministry of Health, Labour and Welfare Notification No.370, Food Sanitation Act.
(Except for fat oil and fatty foods.)

Hose



Structure (Cross-Section View)



Applications

- Water supplying and draining for equipments.
- For piping and drain hose of pneumatic/air-conditioning equipment.
- For washing of ship, vehicle and etc.
- For conveying of powders, grains, chemicals and etc.
- For sprayer.
- For civil engineering and construction.
(Please consult us on hoses for special usage such as shower hoses and etc.)

Sizes and properties (HINET-□)

Nominal Dia. (φ)	I.D. x O.D. (mm)	Working Pressure (20°C) MPa or less/ [kgf/cm ² or less]	Bending Radius (mm or more)	Ref. Weight (g/m)	Std. Length (m)
4	4.0 x 9.0	1.0[10.2]	35	65	100
6	6.0 x 11.0	1.0[10.2]	40	85	
8	8.0 x 13.5	1.0[10.2]	55	110	
9	9.0 x 15.0	1.0[10.2]	60	140	
10	10.0 x 16.0	1.0[10.2]	70	160	
12	12.0 x 18.0	1.0[10.2]	75	170	50, 100
15	15.0 x 22.0	0.8[8.2]	95	245	
19	19.0 x 26.0	0.8[8.2]	135	310	50
25	25.0 x 33.0	0.6[6.1]	165	440	
32	32.0 x 41.0	0.6[6.1]	210	650	
38	38.0 x 48.0	0.5[5.1]	255	840	
50	50.0 x 62.0	0.5[5.1]	380	1,280	40